

## **PRODUCT DATASHEET**

# Surface mounted Panel light HYD-122CR-20W 6500K



# **Application**

- Office
- Kitchen
- Rest room
- Corridor
- Shop

#### **Benefits**

- The light is soft and bright
- Drive stable, safe and reliable
- High light transmission mask to ensure uniform light

#### **Features**

- Efficient and durable
- Easy and quick installation
- Light body thin design, reduce space occupancy
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain





# **Electrical Data**

Nominal wattage (W)	20W	
Nominal Voltage (V)	100-240	
Mains Frequency (Hz)	50	
Nominal Current (mA)	92	
LED Driver Current (mA)	500	
LED Driver Voltage (V)	30-40	
LED Driver Efficiency (%)		
Power Factor λ	0.9	
Total harmonic distortion (%)		
Operating mode	External LED driver	

# **Photometrical data**

1 110 1011101110111 11011		
Luminous flux ±10% (lm)	2315 lm	
Luminous efficacy	116 lm/w	
Color temperature	6500K	
Light color (designation)	Cold White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	739	
Flickering	Flicker	
Beam angle	116 °	






**IES** 



**Dimensions & Weight** 

Diameter (mm)	225
Height (mm)	50
Product weight (g)	601



## **Material & Colors**

Product color	All White
Housing color	White
Body material	Aluminum
Cover material	PC
Mercury content	0.0 mg

**Application & Mounting** 

A 1:	20 45 96		
Ambient temperature range	-20-45 °C		
Temperature range at storage	-25-60 °C		
Type of connection	Screw terminal		
Type of protection	IP20		
Dimmable	225*50 mm		
Mounting type	Surface mounted		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	No		
LED module replaceable	Not replaceable		
With light source	Yes		




**Certificates & Lifespan** 


Life (h)	50,000		
Certificates	CB / ENEC /RoHS		
Standards	ISO9001:2015		


## **Logistical Data**


Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-122CR-20W	48*31*48.5 cm	20	•••	0.07217

# **Installation Method**









## **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release