

PRODUCT DATASHEET

Recessed Down light HYD-216R-10W 4000K



Application

- Hotel
- Mall
- Lobby
- Theater
- Airport

Benefits

- Flicker free.
- Ra>80, restore the natural color
- Minimum Glare, more clear and comfortable
- Focus the light to highlight the highlights of the space

Features

- Warranty 5 years
- Buckle design, easy and quick installation
- Clear Glass, High light transmission, High light efficiency
- Die-cast aluminum body for better heat dissipation, anti-corrosion

December,30,2023 Product Datasheet HYD-216R-10W 4000K





Electrical Data

Nominal wattage (W)	10W	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50	
Nominal Current (mA)	89	
LED Driver Current (mA)	300	
LED Driver Voltage (V)	30-42	
LED Driver Efficiency (%)	83%	
Power Factor λ	0.5C	
Total harmonic distortion (%)		
Operating mode	External LED driver	

Photometrical data

Luminous flux ±10% (lm)	1083 lm		
Luminous efficacy	103 lm/w		
Color temperature	4000K		
Light color (designation)	Natural White		
Color rendering index Ra	≥80		
Standard deviation of color matching	≤5 SDCM		
Luminous intensity/cd	2260		
Flickering	Flicker free		
Beam angle	32 °		








Dimensions & Weight

Diameter (mm)	120
Height (mm)	65
Product weight (g)	304



Material & Colors

Product color	Black housing / Sand white Frame			
Housing color	Black			
Body material	Aluminum			
Cover material	Glass			
Mercury content	0.0 mg			

Application & Mounting

Ambient temperature range	-20°C~+45 °C	
Temperature range at storage	-20°C~+60 °C	
Type of connection	Screwless terminal	
Type of protection	IP20	
Dimmable	No	
Mounting type	Recesse mounted	
Mounting location	Ceiling	
Application environment	Indoor	
Cut size (mm)	95	
LED module replaceable	Not replaceable	
With light source	Yes	




Certificates & Lifespan

Life (h)	50,000	
Certificates	CB LVD EMC RoHS	
Standards	ISO9001:2015	

Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-216R-10W	64.5*29*40 cm	50		0.07482

Installation Method



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.