

# **PRODUCT DATASHEET**

# Recessed Panel light HYD-P12R-30W 6500K



## Application

- Office
- Kitchen
- Rest room
- Corridor
- Shop

### **Benefits**

- Flicker free.
- The light is soft and bright
- Drive stable, safe and reliable
- High light transmission mask to ensure uniform light

#### Features

- Efficient and durable
- Easy and quick installation
- Light body thin design, reduce space occupancy
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain

January,20,2024 Product Datasheet HYD-P12R-30W 6500K





### **Electrical Data**

Nominal wattage (W)	30W	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50/60 Hz	
Nominal Current (mA)	147	
LED Driver Current (mA)	750	
LED Driver Voltage (V)	24-42	
LED Driver Efficiency (%)	89%	
Power Factor λ	0.95	
Total harmonic distortion (%)	<12%	
Operating mode	External LED driver	

### **Photometrical data**

Luminous flux ±10% (lm)	3053 lm	
Luminous efficacy	99 lm/w	
Color temperature	6500К	
Light color (designation)	Cold White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	1009	
Flickering	Flicker free	
Beam angle	116 °	










## **Dimensions & Weight**

Diameter (mm)	225
Height (mm)	27
Product weight (g)	378



### Material & Colors

Product color	All White	
Housing color	White	
Body material	Aluminum	
Cover material	PC	
Mercury content	0.0 mg	

### **Application & Mounting**

Ambient temperature range	-20°C~+45 °C		
Temperature range at storage	-20°C~+60 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recesse mounted		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	60-205		
LED module replaceable	Not replaceable		
With light source	Yes		

## **Certificates & Lifespan**

Life (h)	50,000	
Certificates	CB LVD EMC RoHS	
Standards	ISO9001:2015	



### Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-P12R-30W	57*26*49.5 cm	20		0.07336

## **Installation Method**



Recessed

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.