

PRODUCT DATASHEET

Recessed Panel light HYD-P7-8W 4000K



Application

- Office
- Kitchen
- Rest room
- Corridor
- Shop

Benefits

- Flicker free.
- The light is soft and bright
- DOB, integrated design, stable structure
- High light transmission mask to ensure uniform light

Features

- Warranty 5 years
- Efficient and durable
- Easy and quick installation
- PC housing and transparent mask material, not easy to deform and change color

May,12,2025 Product Datasheet HYD-P7-8W 4000K





Electrical Data

Nominal wattage (W)	8W
Nominal Voltage (V)	220
Mains Frequency (Hz)	50
Nominal Current (mA)	64
Power Factor λ	0.5
Operating mode	DOB

Photometrical data

Luminous flux ±10% (lm)	561 lm		
Luminous efficacy	76 lm/w		
Color temperature	4000K		
Light color (designation)	Nature White		
Color rendering index Ra	≥80		
Standard deviation of color matching	≤5 SDCM		
Luminous intensity/cd	205		
Flickering	Flicker free		
Beam angle	110 °		






IES

May, 12, 2025 Product Datasheet HYD-P7-8W 4000K



Dimensions & Weight

Diameter (mm)	117
Height (mm)	25
Product weight (g)	71



D 117mm

Material & Colors

Product color	All White	
Housing color	White	
Body material	PC	
Cover material	PC	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-10°C~+40 °C	
Temperature range at storage	-10°C~+40 °C	
Type of connection	Screwless terminal	
Type of protection	IP20	
Dimmable	No	
Mounting type	Recesse mounted	
Mounting location	Ceiling	
Application environment	Indoor	
Cut size (mm)	95	
LED module replaceable	Not replaceable	
With light source	Yes	




Certificates & Lifespan

Life (h)	50,000	
Certificates	CB LVD EMC RoHS	
Standards	ISO9001:2015	

Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-P7-8W	64.5*22*52.5 cm	100	•••	0.07450

Installation Method



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release