

PRODUCT DATASHEET

High light efficiency Recessed Down light HYD-219C-30W 3K/4K/6K



Application

- Hotel
- Mall
- Lobby
- Theater
- Airport

Benefits

- · Flicker free.
- Low lumen depreciation.
- Minimum Glare, more clear and comfortable
- White inner cup, improve light efficiency, increase brightness

Features

- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain
- Yellowing-resistant diffuser (PC)
- Buckle design, easy and quick installation
- Warranty 5 years





Electrical Data

Nominal wattage (W)	30 W
Nominal Voltage (V)	220-240 V
Mains Frequency (Hz)	50
Nominal Current (mA)	134
LED Driver Current (mA)	750
LED Driver Voltage (V)	24-42
LED Driver Efficiency (%)	87%
Power Factor λ	0.95
Total harmonic distortion (%)	
Operating mode	External LED driver

Photometrical data

Luminous flux ±10% (lm)	3338.1	3338.1 3709	
Luminous efficacy (lm/w)	119.7	133	146.3
Color temperature	3000K	3000K 4000K	
Light color (designation)	Warm White	Nature White	Cold White
Color rendering index Ra	≥80		
Standard deviation of color matching	≤5 SDCM		
Luminous intensity/cd	2045		
Flickering	Flicker free		
Beam angle	84 °		






Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

IES



Dimensions & Weight

Diameter (mm)	185
Height (mm)	95
Product weight (g)	



Material & Colors

Product color	White Lamp cup / Brown Housing		
Housing color	Brown		
Body material	Aluminum		
Cover material	PC		
Mercury content	0.0 mg		

Application & Mounting

Ambient temperature range	-10°C~+40 °C	
Temperature range at storage	-10°C~+40 °C	
Type of connection	Screwless terminal	
Type of protection	IP20	
Dimmable	No	
Mounting type	Recessed mounted	
Mounting location	Ceiling	
Application environment	Indoor	
Cut size (mm)	165	
LED module replaceable	Not replaceable	
With light source	Yes	




Certificates & Lifespan

Life (h)	50,000	
Certificates	CB LVD EMC RoHS	
Standards	ISO9001:2015	

Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-219C-30W	62*42*42.5 cm	20		0.11067

Installation Method



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release