


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 72.87 lm/W
MODEL	P7	I _{max} (cd)	197.2	S/MH(C0/180)	1.25	
NOMINAL POWER(W)	8	LOR(%)	100.0	S/MH(C90/270)	1.24	
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	540.50	η UP,DN(C0-180)	0.0,49.3	
NOMINAL FLUX(lm)	540.505	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.7	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	219.5	η down(%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	192.1	192.6	193.0	193.7	194.2	193.8	193.5	192.6	0- 10	18.63	18.63	3.45,3.45
20	179.6	180.4	181.4	182.7	183.5	182.9	182.3	180.7	10- 20	53.12	71.75	13.3,13.3
30	160.9	162.1	163.4	165.2	166.1	165.4	164.7	162.5	20- 30	79.91	151.7	28.1,28.1
40	137.2	138.6	140.3	142.4	143.5	142.8	142.0	139.2	30- 40	95.59	247.2	45.7,45.7
50	109.8	111.3	112.9	115.6	116.9	116.1	115.2	112.0	40- 50	98.46	345.7	64,64
60	79.36	79.76	80.89	85.51	87.01	86.21	85.14	81.69	50- 60	88.28	434.0	80.3,80.3
70	46.87	45.54	45.48	51.38	54.76	54.09	52.71	49.32	60- 70	66.02	500.0	92.5,92.5
80	16.20	12.58	10.76	16.40	23.12	20.86	17.16	16.20	70- 80	34.99	535.0	99,99
90	0.2137	0.2096	0.2005	0.1956	0.3523	0.2336	0.2248	0.2445	80- 90	5.516	540.5	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 296.94 lm

%lum = 54.9%

%lamp = 54.9%

Conical surface Flux(130deg): 470.44 lm

%lum = 87.0%

%lamp = 87.0%

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3°C
 Operators:DAMIN
 Test Date:2024-03-07

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
 Humidity:65.0%
 Test Distance:9.401m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz

Lamp Flux:540.505x1 lm

NAME:

TYPE:

WEIGHT:

SPEC.: 3000K

DIM.:

SERIAL No.:


MFR.: EVERFINE

SUR.:

Shielding Angle:

LUMINANCE LIMITATION CURVES

GLARE	CLASS	ILLUMINANCE (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	4634	466
80	9727	6139
75	12473	10544
70	14289	13178
65	15584	14865
60	16551	16032
55	17260	16840
50	17810	17404
45	18275	17827


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Coefficients of Utilization(CU)														
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00														
1.0	1.05	1.00	.97	1.02	.98	.95	.98	.95	.92	.94	.92	.89	.91	.88	.87	.85														
2.0	.91	.85	.79	.89	.83	.78	.86	.81	.76	.83	.78	.74	.79	.76	.73	.71														
3.0	.80	.72	.66	.79	.71	.65	.76	.69	.64	.73	.67	.63	.70	.66	.62	.60														
4.0	.71	.62	.56	.70	.62	.55	.67	.60	.54	.65	.59	.54	.63	.57	.53	.51														
5.0	.63	.55	.48	.62	.54	.48	.60	.53	.47	.58	.52	.47	.56	.51	.46	.44														
6.0	.57	.48	.42	.56	.48	.42	.54	.47	.41	.53	.46	.41	.51	.45	.41	.38														
7.0	.52	.43	.37	.51	.43	.37	.49	.42	.37	.48	.41	.36	.47	.41	.36	.34														
8.0	.47	.39	.33	.47	.38	.33	.45	.38	.33	.44	.37	.32	.43	.37	.32	.30														
9.0	.43	.35	.30	.43	.35	.30	.42	.34	.29	.41	.34	.29	.40	.34	.29	.27														
10.0	.40	.32	.27	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.26	.25														



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.298	.169	.054	.291	.166	.053	.277	.159	.051	.265	.153	.049	.254	.147	.047		
2.0	.284	.156	.048	.278	.153	.047	.267	.148	.046	.256	.143	.045	.246	.139	.044		
3.0	.265	.141	.042	.259	.139	.042	.249	.135	.041	.240	.131	.040	.231	.128	.040		
4.0	.246	.128	.038	.241	.126	.037	.232	.123	.037	.223	.120	.036	.215	.117	.036		
5.0	.228	.116	.034	.223	.115	.033	.215	.112	.033	.208	.110	.033	.201	.107	.032		
6.0	.211	.106	.030	.208	.105	.030	.200	.103	.030	.194	.101	.030	.187	.099	.029		
7.0	.197	.097	.028	.194	.097	.028	.187	.095	.027	.181	.093	.027	.176	.091	.027		
8.0	.184	.090	.025	.181	.089	.025	.175	.088	.025	.170	.086	.025	.165	.085	.025		
9.0	.173	.084	.023	.170	.083	.023	.165	.082	.023	.160	.080	.023	.155	.079	.023		
10.0	.163	.078	.022	.160	.077	.022	.155	.076	.021	.151	.075	.021	.147	.074	.021		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)										
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020		
1.0	.179	.156	.135	.154	.134	.116	.105	.092	.081	.060	.053	.047	.019	.017	.015		
2.0	.171	.132	.099	.147	.114	.086	.101	.079	.060	.058	.046	.035	.019	.015	.011		
3.0	.164	.114	.075	.140	.099	.065	.096	.068	.046	.056	.040	.027	.018	.013	.009		
4.0	.156	.101	.059	.134	.087	.051	.092	.061	.036	.053	.036	.021	.017	.012	.007		
5.0	.149	.090	.048	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006		
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005		
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004		
8.0	.128	.069	.029	.111	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004		
9.0	.122	.064	.025	.105	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003		
10.0	.117	.060	.023	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm											
NAME:			TYPE:			WEIGHT:					
SPEC.: 3000K			DIM.:			SERIAL No.:					
MFR.: EVERFINE			SUR.:			Shielding Angle:					
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	2H	24.8	26.3	25.1	26.5	26.7	24.7	26.2	25.0	26.4	26.6
	3H	26.2	27.6	26.5	27.9	28.1	26.0	27.4	26.3	27.6	27.9
	4H	26.7	28.1	27.0	28.3	28.6	26.4	27.7	26.7	28.0	28.2
	6H	27.0	28.3	27.3	28.5	28.8	26.5	27.8	26.9	28.0	28.3
	8H	27.1	28.3	27.4	28.5	28.8	26.5	27.7	26.8	28.0	28.3
	12H	27.0	28.2	27.4	28.5	28.8	26.5	27.6	26.8	27.9	28.2
4H	2H	25.4	26.7	25.7	26.9	27.2	25.3	26.6	25.6	26.8	27.1
	3H	26.9	28.1	27.3	28.4	28.7	26.7	27.9	27.1	28.2	28.5
	4H	27.5	28.6	27.9	28.9	29.2	27.2	28.2	27.6	28.6	28.9
	6H	27.9	28.8	28.3	29.2	29.5	27.4	28.3	27.8	28.7	29.0
	8H	28.0	28.8	28.4	29.2	29.6	27.4	28.3	27.8	28.6	29.0
	12H	28.0	28.8	28.4	29.2	29.6	27.3	28.1	27.8	28.5	28.9
8H	4H	27.7	28.5	28.1	28.9	29.3	27.4	28.2	27.8	28.6	29.0
	6H	28.1	28.8	28.6	29.2	29.7	27.6	28.3	28.1	28.8	29.2
	8H	28.2	28.9	28.7	29.3	29.7	27.6	28.3	28.1	28.7	29.1
	12H	28.3	28.8	28.7	29.3	29.7	27.6	28.1	28.1	28.6	29.1
12H	4H	27.6	28.4	28.1	28.8	29.2	27.3	28.1	27.8	28.5	28.9
	6H	28.1	28.7	28.6	29.2	29.6	27.6	28.3	28.1	28.7	29.1
	8H	28.2	28.8	28.7	29.2	29.7	27.6	28.2	28.1	28.6	29.1
Variations with the observer position at spacings(CIE Pub.117):											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4					
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.3					

CIE Pub.117, 540.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.1)
Area: 0.01 m2

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	57	46	40	56	46	39	33
0.80	68	57	49	67	56	49	65	56	49	42
1.00	77	66	59	76	65	58	73	67	58	51
1.25	84	73	66	82	73	66	80	71	65	58
1.50	89	79	72	87	78	72	84	76	71	63
2.00	96	87	81	94	86	80	90	84	79	71
2.50	99	92	86	97	91	85	94	88	83	75
3.00	103	96	91	101	95	90	97	92	88	79
4.00	107	101	97	104	100	95	100	96	93	84
5.00	109	105	101	107	103	99	102	99	96	87
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators: DAMIN
Test Date: 2024-03-07

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity: 65.0%
Test Distance: 9.401m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	15879
L_0~180 (75) av	13425
L_0~180 (85) av	7333
L_90~270 (65) av	15684
L_90~270 (75) av	12128
L_90~270 (85) av	1226
L_45 (65) av	15827
L_45 (75) av	12831
L_45 (85) av	2448

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2024-03-07

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators: DAMIN
 Test Date: 2024-03-07

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.00.473
 Humidity: 65.0%
 Test Distance: 9.401m [K=1.0000]
 Remarks:

Test:U:220.44V I:0.0645A P:7.4175W PF:0.5213 Freq:50.00Hz Lamp Flux:540.505x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.: 3000K	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.:	Shielding Angle:

UNIT: cd

[illegible]

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.473
Humidity:65.0%
Test Distance:9.401m [K=1.0000]
Remarks:

```